	Туре	Hits		DBs	
1	BRS	2509	702/57,64,69,81,84,189,190,191,191,193,for.103,for.104,for.105,for.106,for.155,for.160.ccls.	USPAT; US-PGPU JPO; DE IBM_TDB	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
Ν	BRS	2439	330/267,268,288,290,296.cc	USPAT; US-PGPU JPO; DE IBM_TDB	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
ω	BRS	1793	327/538,540,547.ccls.	USPAT; US-PGP JPO; D IBM_TD	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB
4	BRS	2183	323/312,313,314,315,317.cc ls.	USF JPC JPC	USPAT; US-PGPUB; EPO;2004/02/26 JPO; DERWENT; 10:51 IBM_TDB
ហ	BRS	0	(determin\$3 or measur\$3) with current with driver adj curcuitry	US UP SD	USPAT; US-PGPUB; EPO;2004/02/26 JPO; DERWENT; 10:31 IBM_TDB
٥	BRS	21	(determin\$3 or measur\$3) with current with driver adj circuitry	ar ar sn	USPAT; US-PGPUB; EPO; 2004/02/26 JPO; DERWENT; 10:32 IBM_TDB

Type Hits	7 BRS 0	8 BRS 4	9 BRS 0	j j)	10 BRS 64	BRS
ts Search Text	(determin\$3 or measur\$3) with current with driver adj circuitry and impedance with reference	(determin\$3 or measur\$3) with current with driver adj circuitry and impedance	accurate with (determin\$5 or measur\$5) with suppl\$3 with current and driver adj circuitry and	impedance	impedance accurate with (determin\$5 or measur\$5) with suppl\$3 with current and impedance	impedance accurate with (determin\$5 or measur\$5) with suppl\$3 with current and impedance accurate with (determin\$5 or measur\$5) with suppl\$3 with current and impedance with (reference or predetermin\$3 or predetermin\$3 or predefin\$2 or preset\$4 or threshold\$1)
DBs	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB		TBM_'I'DB	O .	USPAT; USPAT; US-PGPUB; EF JPO; DERWENT e USPAT; e US-PGPUB; EF JPO; DERWENT IBM_TDB
Time Stamp	;2004/02/26 10:32	;2004/02/26 10:35	; 2004/02/26	10:37	10:37 ; 2004/02/26 10:37	10:37 ; 2004/02/26 ; 2004/02/26 ; 10:38
Comments						
Error Definiti on						

		10:59	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	measur\$5 with suppl\$3 with current with (driver or integrated) with circuit\$2	443	BRS	17
		2004/02/26	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	measur\$5 with cuppl\$3 with current with (driver or integrated) with circuit\$2	0	BRS	16
		2004/02/26 10:58	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	USPAT; 323/312,313,314,315,317.cc US-PGPUB; EPO; ls. IBM_TDB	2273	BRS	15
		2004/02/26 10:50	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	327/538,540,547.ccls.	1890	BRS	14
		2004/02/26 10:50	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	330/267,268,288,290,296.cc ls.	2499	BRS	13
Error Definiti on	Comments	Time Stamp	DBs	Search Text	Hits	Туре	

	Туре	Hits	Search Text 5 with suppls		DBs
18	BRS	0	with suppl\$3 with with (driver or ed) with circuit\$2 ar\$4 with impedance ference\$1 or d\$1 or min\$3 or preset\$4 fin\$2)	USPAT; US-PGPUB; EPO JPO; DERWENT;	; EPO; WENT;
19	BRS	δ	measur\$5 with suppl\$3 with current with (driver or integrated) with circuit\$2 and compar\$4 with impedance with (reference\$1 or threshold\$1 or predetermin\$3 or preset\$4 or predefin\$2)	USPAT; US-PGPUB; JPO; DERW IBM_TDB	T; GPUB; EPO; DERWENT; TDB
20	BRS	325 325	current with measur\$5 with precision with resistor\$1	USPAT; US-PGPUB; E JPO; DERWEN IBM_TDB	; EPO;
21	BRS	Ν	current with measur\$5 with precision with resistor\$1 and compar\$4 with impedance with (reference\$1 or threshold\$1 or predetermin\$3 or preset\$4 or predefin\$2)	USPAT; US-PGPUB; EPC JPO; DERWENT; IBM_TDB	3; EPO;

24 B	23 B	22 B	
BRS	BRS :	BRS	Туре
10	114	20	Hits
USPAT; core adj power with supply US-PGPUB; adj power IBM_TDB	core adj power and supply adj power	current with measur\$5 with precision with resistor\$1 and impedance with (reference\$1 or threshold\$1 or predetermin\$3 or preset\$4 or predefin\$2)	Search Text
USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	DBs
2004/02/26 14:24	2004/02/26 14:24	2004/02/26	Time Stamp
			Comments
			Error Definiti on